

Since 1969

Industrial Pressure Washers, Parts Washers and Waste Oil Heaters ...Built Right to Do the Job Right

The Only Portable Hot Water Pressure Washer that Delivers 200°F Cleaning at up to 10 GPM

Pre-plumbed with 3-Way Valve to bypass float tank when drawing water directly from an auxiliary tank. ■ Extra-large **Heating Coil** made of cold-rolled, 3/4" Schedule 80 steel pipe with 5-year warranty; features **Stainless Steel Top Wrap;** unique lift-out design for easy and quick **Coil Access**.

SLX-SLT

- Dual-Gun Ready
- Powered by Gasoline or Diesel; Diesel-Heated
- Belt-Drive Landa Pump with 7-Year Warranty
- 3/4" Schedule 80 Coil

Rugged 2" x 4" x ½" thick box steel frame, with compact footprint, shields key components; further protected by weather-resistant Epoxy Powder Coat finish; Power Platform is vibration isolated to minimize frame stress.

> Water-resistant, metal **Control Panel** has adjustable thermostat, combination hour meter and tachometer, volt meter, burner switch and tri-lingual operating instructions for added safety.

> > Adjustable **Detergent** and **Steam Valves** provide precise metering of soap and on-demand wet-steam cleaning.

■ Gasoline-powered Vanguard and Honda Engines, or watercooled, 16-27 hp diesel Lombardini Engine all come with keyed electric starter for easy start-up and protection against unauthorized use; polyurethane Battery Box with vibration isolators protects and firmly secures battery (battery not included).

> Efficient 2,000-Watt Generator produces reliable power for burner.

secures battery not included).

9001

www.landa.com



▲ Industrial-duty tri-plunger Landa Pump designed to run at low RPM for long life, 7-year warranty, with single-rail true-track Pulley Adjustment.

Illustrated
Warning Labels uni-

versally understandable for liability protection.

■ 30-gallon diesel and 16-gallon gasoline Fuel Tanks (15-gallon diesel and 10-gallon gasoline on SLT) provide hours of uninterrupted operation; with elevated fuel lines to avoid suctioning of settled debris.

■ 50 ft. of double-wire braid High Pressure Hose

rated for up to 6000 PSI and featuring a 24-inch safety hose guard for operator burst protection.

■ High-efficiency **Burner**, with dual rings for "dialing in" air flow, has a **Fuel-Water Separator** for fuel pump protection.



Many Safety Features, including a rupture disk, thermal pump protector, flow switch, unloader valve, and safety lock on the trigger gun. Corrosion-resistant Float Tank has stainless steel inlet filter and 3/4" float valve with anti-siphon backflow protection; also allows for introduction of detergents in highpressure mode.



ANDA

Industrial Pressure Washers, Parts Washers and Waste Oil Heaters ...Built Right to Do the Job Right

Since 1969

The Only Portable Hot Water Pressure Washer that Delivers 200°F Cleaning at up to 10 GPM

■ Dual-Gun Ready

- Powered by Gasoline or Diesel; Diesel-Heated
- Belt-Drive Landa Pump with 7-Year Warranty
- 3/4" Schedule 80 Coil

WHY CHOOSE LANDA's SLX or SLT

LANDA®

When it comes to heavy-duty grease or grime, most high-volume, hot water pressure washers fall short with their 150°F water. Landa's SLX, and smaller SLT, are the first power washers ever designed to deliver a high-volume flow at 200°F water, hot enough to melt the toughest of oily messes. The SLX delivers enough hot water flow—up to 9.9 GPM— that you can operate two spray guns at the same time! Other benefits include:

QUALITY: Packed with Landa quality throughout, the SLX and SLT feature a top-of-the-line, belt-drive Landa Pump with 7-year warranty and low RPM for extended life, as well as a giant Schedule 80 heating coil, made of up to 300 ft. of ³/₄-inch steel pipe with 5-year warranty.

DURABILITY: Extraordinarily rugged frame is made of 2-by-4-inch box steel with an all-metal power platform cushioned by 10 vibration isolators to minimize frame stress.

EFFICIENT: The SLX-SLT is heated by a high-efficiency Beckett burner with dual rings for dial-in air flow. The 3/4" heating coil is amazingly efficient due to its unique "breathing" design so it heats quieter while promoting optimum heat exchange.

FUNCTIONAL: The SLX-SLT has a remarkably compact footprint, is certified to UL-1776 safety standards, is pre-plumbed for drawing water from an auxiliary tank, has six forklift guides for portability and the control panel is ideally positioned for curb access when the unit is mounted on a trailer or truck bed.

SLX-SLT

SLX and SLT Specifications

<u>Model No.</u> SLX10-25324E	<u>GPM</u> 9.5	<u>PSI</u> 2500	<u>Engine</u> Honda	<u>НР</u> 24	Engine <u>Fuel</u> Gasoline	Gas <u>Tank</u> 16	Diesel <u>Tank</u> 30	<u>Pump RPM</u> 1560	<u>BTU's</u> 887,000	<u>L x W x H</u> 65" x 36" x 58"	<u>SHIP WT.</u> 2020 lbs.
SLX10-25824E	9.5	2500	Lombardini	27	Diesel	N/A	40	1470	887,000	65" x 36" x 58"	2160 lbs.
SLT5-30224E	5.2	3000	Vanguard	16	Gasoline	10	15	1295	485,000	55" x 32" x 51"	1210 lbs.
SLT6-32324E	5.9	3200	Honda	20	Gasoline	10	15	1570	550,000	55" x 32" x 51"	1220 lbs.
SLT8-30324E	7.8	3000	Honda	24	Gasoline	10	15	1470	728,000	55" x 32" x 51"	1230 lbs.
SLT5-30824E	4.4	3000	Lombardini	16	Diesel	N/A	26	1295	410,000	62" x 32" x 53.5"	1715 lbs.
SLT6-32824E	6.3	3200	Lombardini	27	Diesel	N/A	26	1470	588,000	62" x 32" x 53.5"	1785 lbs.
SLT8-30824E E=Electric Start	7.8	3000	Lombardini	27	Diesel	N/A	26	1560	728,000	62" x 32" x 53.5"	1850 lbs.

Note: We are constantly improving and updating our products. Consequently, pictures, features, and specifications in this brochure may differ slightly from current models. Flow rates and pressure ratings may vary due to variances allowed by manufacturers of our machine components. We attempt to keep our machine performance within ±5% of listed specifications.





Power Wash Detergents: Landa has an extensive line of detergents formulated specifically for use with hot water pressure washers such as the SLX and SLT

www.landa.com

