

A-6 Synthetic Detergent

Multi-Purpose Cleaner

Engineered Specifically for Pressure Washers

A fast-acting, butyl-based detergent for removing grease, oil and road film from tractor-trailers. Safe to use on aluminum, stainless-steel, glass, paint and even fine automotive paint finishes when used as directed.

APPLICATIONS:

- ▶ Tractor-Trailers
- ▶ Engine Degreasing
- ▶ Farm Equipment
- ▶ Floors
- ▶ Food Processing

Other applications: Heavy equipment, cars, trucks, RVs, floors, walls, building exteriors, tanks, tanker trucks, railroad cars, buses, airport runways

FEATURES / USER BENEFITS

- ▶ USDA Approved

HIGH DILUTION RATIO

- ▶ Up to 100 to 1 means more economical cost-in-use

BIODEGRADABLE

- ▶ Environmentally Friendly

VERSATILE

- ▶ Works with hard or soft water

FAST ACTING

- ▶ Formulated to cut grease and suspend oils quickly

DEEP CLEANING

- ▶ Butyl-based blend delivers deep cleaning action



Available In	Description	Stock#
5-Gal. Pail	Liquid Concentrate	01-00B
55-Gal. Drum	Liquid Concentrate	01-00D
Bulk	Liquid Concentrate	01-00E

Ask about our Silver Service Maintenance Programs offered with bulk soap purchases.

A-6 Synthetic Detergent

Multi-Purpose Cleaner

Engineered Specifically for Pressure Washers

SPECIAL FEATURES:

A-6 is a strong, highly concentrated, butyl-based vehicle detergent formulated to quickly and effectively remove dirt, grime, grease and road film from all types of road vehicles.

It is engineered to be metered through a hot- or cold-water pressure washer or can be applied as a presoak thru a WET™ sprayer or foam applicator. The dilution ratio makes the cost-in-use very economical.

A-6 can be used safely on virtually every surface, including aluminum, stainless steel, glass, plastic, paint and fine automotive paint finishes when used as directed.

A-6 is ideal for vehicle wash facilities where it can be used on tractor-trailers, heavy equipment, shop floors, metal or plastic tanks, RVs, trucks, and autos.

DIRECTIONS FOR USE

Read Material Safety Data Sheet thoroughly before using this product.

Apply with a Hot or Cold Water Pressure Washer: Pressure washers use an injector and mix the detergent into the water spray. Consult your WET™ dealer for detergent metering specifications. When using a pressure washer, wash from the bottom up (applying detergent) and rinse from the top down.

CAUTION

May cause eye burns. Avoid prolonged or repeated contact with skin. Harmful if swallowed. Use with adequate ventilation.

FIRST AID

EYES: Immediately flush with water for 15 minutes. Get medical attention immediately.

SKIN: Wash thoroughly with water. Get medical attention if irritation persists.

INTERNAL: DO NOT induce vomiting. Drink water. Get medical attention immediately.

**KEEP OUT OF REACH
OF CHILDREN**

**FOR INSTITUTIONAL AND
INDUSTRIAL USE ONLY**

LABEL INSTRUCTIONS

Health	2
Flammability	0
Reactivity	1
Personal Protection	2

Degree of Hazard: 4-Very High, 3-High, 2-Moderate, 1-Slight, 0-Insignificant.

INGREDIENTS

Water (CAS#7732-18-5), Glycol Ether EB (CAS#IN-70-2), Sodium Metasilicate (CAS#6834-92-0)

For medical emergency call:

Rocky Mountain Poison Center - 303-623-5716

For emergency spills call: Chemtrec - 1-800-424-9300

Outside U.S. call: 703-527-3887

TECHNICAL DATA

Specific Gravity	1.02
pH (5% Solution)	12.1-12.3
Boiling Point	> 212° F
Vapor Pressure	23mm/hg@70° F
Vapor Density (Air=1)	1.2
VOC Content	Trace
Solubility in Water	Soluble
Reactivity in Water	None
Melting Point	32° F
Foam Level	170-180 ml
Total Alkalinity9-1.0 ml
Freeze Thaw Stable	Yes
Hard Water Stable	Yes
Insolubles	None
Shelf Life	1-Yr Min. in closed container

This product contains less than 2 grams of VOC per liter.



Corporate Headquarters

4810 IH 10 East
San Antonio, TX 78219
210-662-9744

Corpus Christi Operations

1737 N. Lexington Blvd.
Corpus Christi, TX 78408
361-289-8824

Valley Operations

2813 N. Expressway 83 Ste-C
La Feria, TX 78559
956-412-7257

El Paso Operations

3465 Lee Blvd, Ste. 241
El Paso, TX 77936
915-592-3375

800-899-9388 • Fax: 210-662-9794

www.wet-inc.com • Email: getclean@wet-inc.com