Super Red

Truck Wash Plus

Engineered Specifically for Pressure Washers

A fast-acting, detergent for removing grease, oil and road film from tractor-trailers. Safe to use on aluminum, stainless-steel, glass, paint and even fine automotive paint finishes.

APPLICATIONS:

- Tractor-Trailers
- Engine Degreasing
- Farm Equipment
- ▶ Floors

FEATURES / USER BENEFITS CORROSION INHIBITORS

> Safe to use; protects your power washer

HIGH DII UTION RATIC

Up to 80 to 1 means more economical cost-in-use

BIODEGRADABI E

➤ Environmentally Friendly

VERSATILE

Works with hard or soft water

FAST ACTING

Cuts road film and suspends oils quickly

Deep Cleaning

Special blend delivers deep cleaning action

CORROSION INHIBITORS

Helps prevent flash rusting





Available In	Description	Stock#
50 lb box	Powder	01-74A
100 lb drum	Powder	01-74B
400 lb drum	Powder	01-74C

Super Red Truck Wash Plus

Engineered Specifically for Pressure Washers

SPECIAL FEATURES:

Super Red is a strong, highly concentrated, vehicle detergent formulated to quickly and effectively remove dirt, grime, grease and road film from all types of road vehicles. Super Red is biodegradeable.

It is engineered specifically to be metered through a hot- or cold- pressure washer. The dilution ratio makes the cost-in-use very economical.

Super Red can be used safely on virtually every surface, including aluminum, stainless steel, glass, plastic and fine automotive paint finishes.

DIRECTIONS FOR USE

Read Material Safety Data Sheet thoroughly before using this product.

CAUTION

May cause eye burns. Avoid prolonged or repeated contact with skin. Harmful if swallowed. Use with adequate ventilation.

FIRST AID

EYES: Immediately flush with water for 15 minutes. Get medical attention immediately.

SKIN: wash thoroughly with water. Get medical attention if irritation persists.

INTERNAL: DO NOT induce vomiting. Drink water. Call physician immediately.

KEEP OUT OF REACH OF CHILDREN

FOR INSTITUTIONAL AND **INDUSTRIAL USE ONLY**

Health	2
Flammability	0
Reactivity	
Personal Protection	
Degree of Hazard: 1-Very High 3-High	

Glycol Ether (CAS#111-76-2), Sodium Matasilicate (CAS#6834-92-0)

For medical emergency call:

Rocky Mountain Poison Center - 303-623-5716

For emergency spills call: Chemtrec - 1-800-424-9300

Outside U.S. call: 703-527-3887

Specific Gravity	1.02
Boiling Point	> 212º F
% Volatiles by Volume	
Vapor Pressure	
Vapor Density (Air=1)	· · · · · · · · · · · · · · · · · · ·
VOC Content	
Solubility in Water	Soluble
Reactivity in Water Melting Point	32º F
Foam Level	
Total Alkalinity	9 - 1.0 ml
Freeze Thaw Stable	
Hard Water Stable	Yes
Insolubles	None
Shelf Life	

This product contains less than 2 grams of VOC per liter.



Corporate Headquarters

4810 IH 10 East San Antonio, TX 78219 210-662-9744

Corpus Christi Operations

1737 N. Lexington Blvd. Corpus Christi, TX 78408 361-289-8824

Valley Operations

2813 N. Expressway 83 Ste-C La Feria, TX 78559 956-412-7257

El Paso Operations

3465 Lee Blvd. Ste. 241 El Paso, TX 77936 915-592-3375

800-899-9388 • Fax: 210-662-9794

www.wet-inc.com • Email: getclean@wet-inc.com