LANDA®

Industrial Pressure Washers ...Built Right to Do the Job Right

Since 1969

ECOS

Environmentally Friendly Mobile Wash and Reclaim System

- 4.7 GPM at 3500 PSI
- Captures, filters, and recycles wash water for continuous use
- Trans-Heat Technology for better fuel efficiency

- Vacuum/Water Reclaim System with 50 feet of 2-inch vacuum hose and draggable, non-tipping suction head provides continuous suction of wash water.
- Multi-Stage Filter System includes a 40 gal holding tank with a 500 mesh/100 micron Pre-Filter Sock, a 20 micron Pleated Cartridge Filter. a 5 micron Carbon Filter, and an Oil Skimmer Bag. Clean water is directed to selected tanks for reuse, or can be discarded or dumped directly to drain, pending local EPA requirements.
- Honda GX660 Engine and LANDA **LT Pump** with 7-year warranty provide 4.7 GPM at 3500 PSI of cleaning might.
- Heavy-Duty 4,000 Watt Generator produces reliable 120V AC power to the burner and vacuum.
- Durable Swing-Away **Tongue** (rated for 7,500 lbs) with 2-5/16 inch Ball Coupler, 7-pin Electrical Trailer Plug and heavy-duty 2,000 lb. capacity Swivel Jack, allows trailer to be stored in smaller area.

- Patent-Pending Trans-Heat **Technology** captures exhaust from the engine to preheat water increasing water temperatures up to 15°F providing better fuel efficiency.
- **LANDA Duracoil** with stainless steel top wrap and 5-year warranty heats

Conveniently placed Locked Control Panel includes key start, choke, Burner On/Off Switch, Adjustable Thermostat, and an Hour Meter with low oil indicator. Also includes reclaim pump and vacuum motor switches and Low Point Drain for water tanks.

■ Four **Polyethylene Water Tanks** provide 400 gallons of clean water and are linked for even distribution. Main Control Valve System includes easy to use valves for controlling water distribution. Feed Pump with pressuresensing switch alleviates wear and tear on main pump.







■ Two Hose Reels hold up to 100 ft. of highpressure hose and 75 ft. of low-pressure hose.



- 30 in. x 7 ft. Galley with removable gate has storage for Vacuum Hose underneath the floor.
- Insulated, springloaded Trigger Gun and insulated, dual-lance Variable Pressure Wand make it easy to switch between detergent wash and rinse modes.
- Locked compartment includes **Dual Fuel Tanks** for gasoline engine (17 gal.) and diesel burner (17 gal.). Includes space for two detergent buckets.
- Safety Features including redundant devices such as a Rupture Disk, and hightemperature shut down to guard against excessive pressure or heat.
- Four 15-inch Chrome Steel Wheels with 205/75/R15 tires on Tandem Axles rated at 3,500 lbs each (7,000 lbs total) with Electric Brakes on both axles and battery operated Breakaway Kit for added safety.
- Four **Color-Coded Quick-Couple Nozzles** made of hardened stainless steel are mounted near hose reel for ready access.

www.landa.com

LANDA®

Industrial Pressure Washers ...Built Right to Do the Job Right

Since 1969

ECOS

Environmentally Friendly Mobile Wash and Reclaim System

- 4.7 GPM at 3500 PSI
- Captures, filters, and recycles wash water for continuous use
- Trans-Heat Technology for better fuel efficiency



LANDA's revolutionary ECOS Mobile Wash/Reclaim System recovers, cleans and recycles the wash water from pressure washing for safe disposal or reuse—meeting most municipal and environmental regulations.

For a Better Tomorrow... Clean Green with LANDA!

LANDA's revolutionary ECOS Mobile Wash/Reclaim System recovers, cleans and recycles the gray water from pressure washing for safe disposal or reuse-meeting most municipal and environmental regulations. And the fuel burner savings from the patent-pending Trans-Heat Technology allows for a fast return on investment. Call a LANDA Dealer to learn how your fuel savings can help make your lease payment!

For a Better Tomorrow . . . Clean Green with LANDA!

1.103-825.0 Part No

Pressure Washer System

Volume 4.7 GPM Pressure 3.500 PSI

Engine Honda GX660, 688cc Gasoline (17 gallon tank) **Engine Fuel** LANDA LT (1360 RPM) Pump Generator 4.000 watts/120VAC

Wand Assembly Variable pressure wand with 50' hose Detergent Downstream detergent injector

Heating System

Pre-Heating Patent-pending Trans-Heat Technology

Coil 1/2" Schedule 80

Burner Fuel Diesel/kerosene/fuel oil (17 gallon tank)

BTUs 440,000

Vacuum System

Suction 105 CFM Hose 50' x 2" diameter Multi-Stage Filter System

Pre-Filter 500 mesh/100 micron duo-polyester bag

Oil Removal Oil skimmer bag

Sediment 20 micron pleated polyester

Polish 5 micron carbon

Trailer

Water Tank Capacity 400 gallons Load 7,000 lb. capacity

Trailer Axles Dual, 3,500 lbs. each with electric brakes Wheels 15-inch wheels, ST205/75/R15 tires

Swing-Away Tongue 7500 lb. capacity with 2 5/16 inch ball coupler

2,000 lb. capacity **Swivel Jack**

Safety Chains Dual 5/16 inch steel link with latching hooks Lighting DOT Approved Recessed lights, license plate holder 174"L x 75"W x 73 ¹/₂ "H (with swing-away tongue extended) Dimensions

Dimensions w/ pallet 161"L x 85"W x 82"H (pallet & crate)

Distributed by:

ACCESSORIES:

Description

20 micron Pleated Filter Cartridge 5 micron Carbon Filter Cartridge 100 ft. Tuff-Skin 6000 PSI Hose 100 ft. Hose Reel

Rear Drop Down Ramp **Drain Covers** Portable Wash Pads Ladder Rack Water Berms

www.landa.com

Additional Hose Reel Mount