

Super Red II

Truck Wash

Engineered Specifically for Pressure Washers

A fast-acting, non caustic detergent for removing grease, oil and road film from tractor-trailers. Safe to use on aluminum, stainless-steel, glass, paint and even fine automotive paint finishes.

APPLICATIONS:

- ▶ Tractor-Trailers
- ▶ Engine Degreasing
- ▶ Farm Equipment
- ▶ Floors

FEATURES / USER BENEFITS

CORROSION INHIBITORS

- ▶ Safe to use; protects your power washer

HIGH DILUTION RATIO

- ▶ Up to 80 to 1 means more economical cost-in-use

BIODEGRADABLE

- ▶ Environmentally Friendly

VERSATILE

- ▶ Works with hard or soft water; quick-release surfactant compatible with recycling systems. Can be used with hard water and higher dilution ratio with soft water

FAST ACTING

- ▶ Cuts road film and suspends oils quickly

Deep Cleaning

- ▶ Special blend delivers deep cleaning action

CORROSION INHIBITORS

- ▶ Helps prevent flash rusting



Available In	Description	Stock#
5-Gal. Pail	Liquid Concentrate	01-81B
55-Gal. Drum	Liquid Concentrate	01-81D
Bulk	Liquid Concentrate	01-81E

Super Red II

Truck Wash

Engineered Specifically for Pressure Washers

SPECIAL FEATURES:

Super Red II is a strong, highly concentrated, vehicle detergent formulated to quickly and effectively remove dirt, grime, grease and road film from all types of road vehicles. Super Red is biodegradeable.

It is engineered specifically to be metered through a hot- or cold- pressure washer. The dilution ratio makes the cost-in-use very economical.

Super Red II can be used safely on virtually every surface, including aluminum, stainless steel, glass, plastic and fine automotive paint finishes.

DIRECTIONS FOR USE

Read Material Safety Data Sheet thoroughly before using this product.

CAUTION

May cause eye burns. Avoid prolonged or repeated contact with skin. Harmful if swallowed. Use with adequate ventilation.

FIRST AID

EYES: Immediately flush with water for 15 minutes. Get medical attention immediately.

SKIN: wash thoroughly with water. Get medical attention if irritation persists.

INTERNAL: DO NOT induce vomiting. Drink water. Call physician immediately.

KEEP OUT OF REACH OF CHILDREN

FOR INSTITUTIONAL AND INDUSTRIAL USE ONLY

LABEL INSTRUCTIONS

Health	2
Flammability	0
Reactivity	0
Personal Protection	2

Degree of Hazard: 4-Very High, 3-High, 2-Moderate, 1-Slight, 0-Insignificant.

INGREDIENTS

DDBSA (CAS#27176-87-0),

For medical emergency call:

Rocky Mountain Poison Center - 303-623-5716

For emergency spills call: Chemtrec - 1-800-424-9300

Outside U.S. call: 703-527-3887

TECHNICAL DATA

Specific Gravity	1.02
Boiling Point	> 212° F
Vapor Pressure	23mm/hg @ 70° F
Vapor Density (Air=1)	1.2
VOC Content	Trace
Solubility in Water	Soluble
Reactivity in Water	None
Melting Point	32° F
Foam Level	170 - 180 ml
Total Alkalinity	9 - 1.0 ml
Freeze Thaw Stable	Yes
Hard Water Stable	Yes
Insolubles	None
Shelf Life	1-Yr Min. in closed container

This product contains less than 2 grams of VOC per liter.



Corporate Headquarters

4810 IH 10 East
San Antonio, TX 78219
210-662-9744

Corpus Christi Operations

1737 N. Lexington Blvd.
Corpus Christi, TX 78408
361-289-8824

Valley Operations

2813 N. Expressway 83 Ste-C
La Feria, TX 78559
956-412-7257

El Paso Operations

3465 Lee Blvd, Ste. 241
El Paso, TX 77936
915-592-3375

800-899-9388 • Fax: 210-662-9794

www.wet-inc.com • Email: getclean@wet-inc.com