

LANDA®

Since 1969

Industrial Pressure Washers and Parts Washers
...Built Right to Do the Job Right

MHC

Self-Contained, Gasoline-Powered, Diesel-Heated, Hot Water Pressure Washer

- Up to 3.5 GPM, 3500 PSI
- Heavy-Duty Honda or Subaru Robin Engine
- Direct-Drive Landa Pump with 7-Year Warranty
- Sch. 80 Heating Coil



■ Extra-durable **Horizontal Heating Coil** made of leak-free, cold-rolled, Schedule 80 steel pipe with five-year warranty.

■ Unique lift-out design allows for easy and quick **Coil Access**.

■ Top-of-the-line **12V DC Burner** uses new high-tech engineering for better fuel efficiency and lower maintenance.

■ Helpful **Trilingual Labels** with operating instructions in English, Spanish and French for owner and operator protection.



▲ Industrial-grade, tri-plex **Landa High-Pressure Pump** has a forged brass head and a seven-year limited warranty.

■ Easy-reach **Control Panel** has **Adjustable Thermostat, Hour Meter, and Tachometer** with digital display that flashes a reminder when maintenance is due.

■ Industrial-duty **Honda or Subaru Robin Engine**, with overhead valves and easy-access oil drain line, is mounted on **Vibration Isolators** for less wear and longer life.

■ Insulated, fatigue-free **Trigger Gun** and chrome-plated, dual-lance **Variable Pressure Wand** for adjusting of the pressure while cleaning.

■ 50 ft. of steel-wire braid **High Pressure Hose** with 24-inch guard for burst protection.

■ Many **Safety Features**, including a rupture disk and thermal pump protector to prevent build up of excess pressures or heat.

■ Options include **Caster Wheels** for extra mobility in tight work areas and **Float Tank** with inlet detergent metering valve.

■ Easy-to-attach **Detergent Injector** for applying soap while washing simply by twisting the handle on the wand.

■ 13-inch, two-ply, tubed, **Pneumatic Tires** for easy maneuvering and **Wheel Brake** for added stability.

■ Rust-free, 10 gal. **Fuel Tank** with elevated fuel line to prevent dirt and debris from reaching burner.

■ Rugged 1¼" square tube steel **Chassis** protected with weather-resistant epoxy powder coat finish.



▲ Durable polyurethane **Battery Box** on electric start models slides out for easy access.

■ Four quick-couple **Nozzles** are made of hardened stainless steel and mounted for ready access.



www.landa.com

LANDA®

Industrial Pressure Washers and Parts Washers
...Built Right to Do the Job Right

Since 1969

MHC

Self-Contained, Gasoline-Powered,
Diesel-Heated, Hot Water Pressure Washer

- Up to 3.5 GPM, 3500 PSI
- Heavy-Duty Honda or Subaru Robin Engine
- Direct-Drive Landa Pump with 7-Year Warranty
- Sch. 80 Heating Coil



Shown with optional float tank and caster wheel kit

The optional Caster Wheel Kit makes the MHC super mobile and ideal for jobs where the unit will be moved frequently

WHY CHOOSE LANDA'S MHC

The MHC is the most rugged, gasoline-powered, hot water, on-site cleaning machine on wheels featuring a unique blend of quality, safety, serviceability, and extra stability. There are six MHC models to choose from; three models feature electric start and three utilize Landa's proprietary Super Duty Regulator (SDR) which allows the machine to operate completely without a battery or magneto system.

■ **Built to Last:** From the heavy-duty Landa pump and energy-efficient 12 volt burner to the single-piece, welded steel frame and legendary Landa heating coil, the MHC is built to last.

■ **Safe to Use:** In addition to its ETL certification to the rigid UL-1776 safety standards, the MHC has a many safety features, including adjustable thermostat, rupture disk, wheel brake, 24-inch hose guard and tri-lingual operating and warning labels.

■ **Easy to Operate:** The MHC is an operator's dream with variable pressure wand, downstream detergent injection, quick couple nozzles, adjustable thermostat and a digital hour/tachometer that even provides service reminders.

■ **Extra Stable:** Stability is essential for a portable washer like this. With its one-piece fully-welded 1¼-inch steel tube frame, 13-inch tubed all-terrain tires and engine vibration mounts, the MHC is rock solid.

MHC Specifications

| Part No. | GPM | PSI | Engine | HP | Start | Pump RPM | Burner | BTU's | L x W x H | SHIP WT. |
|-----------------|-----|------|--------------|----|----------|----------|--------|---------|---------------------|----------|
| MHC3-24124 | 2.7 | 2400 | Subaru Robin | 7 | Recoil | 3400 | 12V DC | 266,000 | 41.5" x 29" x 44.5" | 485 lbs. |
| MHC3-30324 | 3.0 | 3000 | Honda | 9 | Recoil | 3400 | 12V DC | 266,000 | 41.5" x 29" x 44.5" | 560 lbs. |
| MHC4-30324 | 3.5 | 3000 | Honda | 11 | Recoil | 3400 | 12V DC | 336,000 | 41.5" x 29" x 44.5" | 560 lbs. |
| MHC4-30324E* | 3.5 | 3000 | Honda | 11 | Electric | 3400 | 12V DC | 336,000 | 41.5" x 29" x 44.5" | 565 lbs. |
| MHC4-30324E/S*† | 3.5 | 3000 | Honda | 13 | Electric | 3400 | 12V DC | 336,000 | 41.5" x 29" x 44.5" | 580 lbs. |
| MHC4-35324E* | 3.5 | 3500 | Honda | 13 | Electric | 3400 | 12V DC | 336,000 | 41.5" x 29" x 44.5" | 580 lbs. |

* Electric start model requires battery (not included) † Designed for high altitude applications. Note: We are constantly improving and updating our products. Consequently, pictures, features, and specifications in this brochure may differ slightly from current models. Flow rates and pressure ratings may vary due to variances allowed by manufacturers of our machine components. We attempt to keep our machine performance within ±5% of listed specifications.

LANDA®

Distributed by:

FIELD INSTALLABLE OPTIONS:

| Part No. | Description |
|-------------|---|
| 8.915-404.0 | Caster Wheel Kit (front end) |
| 8.915-406.0 | Float Tank & Inlet Detergent Metering Valve |
| 8.915-496.0 | 360° Pivot Hose Reel Kit (100 ft capacity) |
| 8.916-184.0 | Lifting Bracket |
| 8.915-494.0 | Trailer Mount Kit |

www.landa.com