P-40 Vehicle Cleaner

Engineered Specifically for Pressure Washers

A detergent ideal for removing grease, oil and road film with alcohol for restoring painted surfaces. Safe to use on aluminum, stainless-steel, glass, paint, and even fine automotive paint finishes.

APPLICATIONS:

- Tractor-Trailers
- Automobiles
- > Farm Equipment
- Motorcycles

Other applications: Heavy equipment, RVs, walls, tanks, tanker trucks, railroad cars and buses

FEATURES / USER BENEFITS

 Safe to use; protects your pressure washer

HIGH DILUTION RATIO

Up to 80 to 1 means more economical cost-in-use

BIODEGRADABLE

➤ Environmentally Friendly

VERSAIILE

Works with hard or soft water

FAST ACTING

Formulated to release road film quickly

RESTORATIVE CLEANING

Non-butyl-based blend delivers deep cleaning action





| Available In | Description | Stock# |
|--------------|--------------------|--------|
| 5-Gal. Pail | Liquid Concentrate | 01-66B |
| 55-Gal. Drum | Liquid Concentrate | 01-66D |
| Bulk | Liquid Concentrate | 01-66E |

P-40

Vehicle Cleaner

Engineered Specifically for Pressure Washers

SPECIAL FEATURES:

P-40 is a concentrated, heavy duty, non-butyl vehicle wash formulated to quickly and effectively remove dirt, grime, grease and road film from all types of road vehicles. P-40 is biodegradable.

It is engineered to be metered through a hot- or cold-water pressure washer or can be applied as a presoak thru a **WET**TM sprayer or foam applicator. The dilution ratio makes the cost-in-use very economical.

P-40 can be used safely on virtually every surface, including aluminum, stainless steel, glass, plastic, paint and fine automotive paint finishes.

P-40 is ideal for vehicle wash facilities where it can be used on tractor-trailers, heavy equipment, metal or plastic tanks, RVs, trucks, and autos.

DIRECTIONS FOR USE

Read Material Safety Data Sheet thoroughly before using this product.

Apply with a Hot or Cold Water Pressure Washer: Pressure washers use an injector and mix the detergent into the water spray. Consult your WET™ dealer for detergent metering specifications. When using a pressure washer, wash from the bottom up (applying detergent) and rinse from the top down.

CALITION

May cause eye burns. Avoid prolonged or repeated contact with skin. Harmful if swallowed. Use with adequate ventilation.

FIRST AID

EYES: Immediately flush with water for 15 minutes. Get medical attention immediately.

SKIN: Wash thoroughly with water. Get medical attention if irritation persists.

INTERNAL: DO NOT induce vomiting. Drink water. Get medical attention immediately.

KEEP OUT OF REACH OF CHILDREN

FOR INSTITUTIONAL AND INDUSTRIAL USE ONLY

KEEP FROM FREEZING

LAREL INSTRUCTIONS

| Health | 2 |
|--------------------------------------|---|
| Flammability | 0 |
| Reactivity | |
| Personal Protection | |
| Degree of Hazard: 1-Very High 3-High | |

INGREDIENTS

Water (CAS#7732-18-5), EDTA (CAS#013-235-36-4), Sodium Metasilicate (CAS#6834-92-0), Glycol Ether EB (CAS#111-76-2)

For medical emergency call:

Rocky Mountain Poison Center - 303-623-5716

For emergency spills call: Chemtrec - 1-800-424-9300

Outside U.S. call: 703-527-3887

TECHNICAL DATA

| Specific Gravity | 1.03 |
|-----------------------|-------------------------------|
| Boiling Point | > 212º F |
| Vapor Pressure | |
| Vapor Density (Air=1) | 1.2 |
| VOC Content | Trace |
| Solubility in Water | Soluble |
| Reactivity in Water | None |
| Melting Point | 32º F |
| Foam Level | 150 - 160 ml |
| Total Alkalinity | 1.0 ml |
| Freeze Thaw Stable | Yes |
| Hard Water Stable | |
| Insolubles | None |
| Shelf Life | 1-Yr Min. in closed container |

This product contains 3 grams of VOC per liter.



Corporate Headquarters

4810 IH 10 East San Antonio, TX 78219 210-662-9744

Corpus Christi Operations

1737 N. Lexington Blvd. Corpus Christi, TX 78408 361-289-8824 **Valley Operations**

2813 N. Expressway 83 Ste-C La Feria, TX 78559 956-412-7257

El Paso Operations

3465 Lee Blvd, Ste. 241 El Paso, TX 77936 915-592-3375

800-899-9388 • Fax: 210-662-9794

www.wet-inc.com • Email: getclean@wet-inc.com