

LANDA®

Industrial Pressure Washers and Parts Washers
...Built Right to Do the Job Right

Since 1969

HOT

Portable, Electric-Powered, Diesel-Heated, Hot Water Pressure Washer

- Up to 3.5 GPM, 2000 PSI
- Heavy-Duty Motor
- Sch. 80 Heating Coil
- True Steam Model

■ Heavy-duty **Legacy or Baldor Motor** with **Landa High-Pressure Pump**, which features three ceramic plungers and a forged brass head with 7-year warranty.*



■ High-heat aluminized steel inner wrap surrounds cold-rolled **Heating Coil** made of Schedule 80 steel pipe with five-year warranty.

■ **Stainless Steel Top Wrap** has unique design that allows access to the coil within minutes by simply removing six bolts.*

■ Helpful **Graphics and Tri-Lingual Labels** with operating instructions in English, Spanish and French for added liability protection and operator convenience.

■ High-efficiency **Burner** is protected by a cover and mounted on the end for easy access.

■ Quick-couple **Nozzle** is made of hardened stainless steel and mounted for ready access.

■ 36 ft. of high-grade **Electrical Cord** with Ground Fault Circuit Interrupter on all models for operator safety.

■ Insulated, fatigue-free **Trigger Gun** with dual-lance **Variable Pressure Wand** provide remote change from low-pressure application of soap to high-pressure rinse.*

■ 50 ft. of steel-wire braid **High Pressure Hose** with guard for burst protection.*

▶ Optional, E-Zee **Hose Reel and Lifting Bracket** with compact, easy-wind design for tangle-free handling of hose.



■ Two-ply, tubed **Pneumatic Tires** make for easy maneuvering in any terrain; safety brake prevents rolling.

▶ Optional rust-free **Float Tank** with stainless steel inlet filter and backflow protection with inlet detergent injection.



■ **Adjustable Thermostat** for precise temperature control.

■ Five **Tie Down Points** for safe transport.

■ **Removable Panels** allow for easy access and servicing of pump, motor and unloader.

■ Conveniently located **Control Panel** with 3-position or rocker switch is housed in a water-resistant electrical enclosure.

■ Easy-to-attach **Downstream Detergent Injector** for application of soap.

■ **Many Safety Features**, including a rupture disk and thermal pump protector to prevent the build up of excessive pressures or heat.

*HOT2-11026D, HOT2-15026D and HOT3-30036D have axial pump with 1-year warranty, yellow painted mild-steel top coil wrap, straight-through insulated wand, and 30 ft. of high pressure hose.

www.landa.com

LANDA®

Industrial Pressure Washers and Parts Washers
...Built Right to Do the Job Right

Since 1969

HOT

Portable, Electric-Powered,
Diesel-Heated, Hot Water Pressure Washer

- Up to 3.5 GPM, 2000 PSI
- Heavy-Duty Motor
- Sch. 80 Heating Coil
- True Steam Model

WHY CHOOSE LANDA'S HOT

The HOT is the most economical choice of Landa's electric-powered, diesel-heated hot water pressure washers featuring the heat-efficient horizontal coil. It is also the only line among those with a horizontal coil design that has a true steam cleaner, or steamer—the HOT3-30036D.

QUALITY: The HOT boasts many of the same quality components of other Landa hot water pressure washers, including a tri-plunger high-pressure Landa pump with 7-year warranty (on most models), Schedule 80 heating coil made of 1/2-inch pipe and easy access to pump and motor.

PORTABILITY: All of the HOT models weigh less than 500 lbs. and are evenly balanced on four leak-free, tubed, pneumatic tires for easy maneuvering in any terrain. Waffle grips on the two steering bars add to the HOT's portability.

SAFETY: Certified to the rigid UL-1776 safety standards, the HOT also has many features that make it extremely safe, including motor thermal overload protection, rupture disk attached to the heating coil, thermal pump protector, flow-activated fuel shut-off switch, hose guard for burst protection, and Ground Fault Circuit Interrupter on all models.



HOT2-15026D shown with optional caster wheel kit

HOT Specifications

Model No.	GPM	PSI	Motor HP	Electrical	Amps	Pump	RPM	Temperature	L x W x H	SHIP WT.
HOT2-11026D	2.0	1000	1.5	120V	18	Axial	3450	Up to 200°F	52" x 27" x 33"	425 lbs.
HOT2-15026D	1.9	1500	2	120V	20	Axial	3450	Up to 200°F	52" x 27" x 33"	428 lbs.
HOT2-11024D	2.0	1000	1.5	120V	18	Direct	1725	Up to 200°F	52" x 27" x 33"	434 lbs.
HOT2-15024D	1.9	1500	2	120V	20	Direct	1725	Up to 200°F	52" x 27" x 33"	439 lbs.
HOT3-11024D	2.8	1000	2	120V	20	Direct	1725	Up to 200°F	52" x 27" x 33"	439 lbs.
HOT4-20024A	3.5	2000	5	230V 1 ph	25	Belt	1350	Up to 200°F	52" x 27" x 33"	494 lbs.
HOT4-20024G	3.5	2000	5	208V 1 ph	27	Belt	1350	Up to 200°F	52" x 27" x 33"	494 lbs.
HOT3-30036D Steamer	2.0	300	1.5	120V	12	Axial	3450	300°F	52" x 27" x 33"	425 lbs.

Note: We are constantly improving and updating our products. Consequently, pictures, features, and specifications in this brochure may differ slightly from current models. Flow rates and pressure ratings may vary due to variances allowed by manufacturers of our machine components. We attempt to keep our machine performance within ±5% of listed specifications.

LANDA®

Distributed by:

FIELD INSTALLED OPTIONS

Part No.	Description
8.917-506.0	Float Tank and Inlet Detergent Metering Valve
8.917-541.0	Hose Reel Platform w/ E-Zee Reel & Connecting Plumbing
8.917-522.0	Hose Reel Platform Only
9.804-067.0	E-Zee Hose Reel (holds 100' of 3/8" hose)
8.711-858.0	Cox Hose Reel (holds 175' of 3/8" hose)
8.917-525.0	Caster Wheel Kit
9.802-283.0	Hour Meter

www.landa.com