



TECH DATA



closed when not in use. Protect from freezing. For industrial use only. Read Safety Data Sheets for more information.

Physical Properties:

Form Liquid
Color Straw / Amber
Odor Almond
Foam High
pH 1.5-2.5
Specific Gravity 0.97 - 0.99
Boiling Point 212

Titration Procedure:

N/A

Chemical Name:

Tunnel Presoak

SKU:

2161

Classification:

Powerblend

Package Sizes & Product Numbers:

4x1 case 2161-B4
5 gal 2161-B5
2x2.5 case 2161-C5
15 gal 2161-D15
55 gal 2161-D55

Additional Information:

N/A

Product Description and Purpose:

Tunnel Presoak is a super concentrated surfactant that is to be used as part of a two step frictionless system. Specifically designed for presoaks in a tunnel carwash

Authorization/Discussion:

N/A

Features and Benefits:

SUPER Concentrated
Advanced Polymer European Surfactant Technology
Melts Bugs and Removes Windshield Eyebrows

Surfaces Applicable:

Vehicle Exteriors

General Usage Directions:

Draw with your choice Powerblend Foundation in a two part process. Power Blend Tunnel Presoak should be used with a tan 36inch capillary tube. Total usage per car should be 4 - 8 ml

Caution:

Keep out of reach of children. Keep container tightly